

### DESCRIPTION:

Rymax Styx UTTO 80W is an outstanding multifunctional mineral hydraulic and transmission oil for tractors. They are suitable for tractors that need one lubricant for the hydraulic system, the transmission, differential, wet brakes and clutches. Styx UTTO is formulated from mineral base oils with special additives to improve viscometrics, it contains anti friction and extreme pressure to prevent wear and tear of metal surfaces at high revs and heavy loads. Styx UTTO is suitable for all modern tractors. Styx UTTO is also available in SAE 85W.

**Styx UTTO is not an engine oil.**

### BENEFITS:

- Optimized clutch performance due to excellent frictional properties
- Prevents from stick-slip and the accompanied noise, all year round
- Very good shear stability
- Excellent protection against wear and corrosion.
- Very good anti-foam properties



### PERFORMANCE LEVELS:

- API GL-4
- Allison C-4
- Caterpillar TO-2
- Case MS 1206
- Case MS 1207
- Case MS 1209
- Case MS 1210
- CNH MAT 3525/3526
- Denison HF (-0-2)
- DIN 51524-3
- Eaton M2950S/I-280-S
- Ford M2C134D
- Ford M2C86B/M2C86A
- JCB 4000/0500 – JCB 4000/2200
- JCMAS HK P-041
- John Deere J20C/J20A
- Kubota: UDT fluid
- MF M1135/M1143/M1145
- NH410B/420A
- Sauer Sundstrand/ Danfoss
- Volvo WB101 (97303)
- Valtra G2-08/G2-B10
- White: Q-1826
- ZF TE-ML 03E/05F/06K/17E/21F

### TYPICAL PROPERTIES

SAE	Unit	80W
Density 15 °C	Kg/m <sup>3</sup>	875
Viscosity 40 °C	cSt	58.2
Viscosity 100 °C	cSt	9.8
Viscosity Index		154
Pour Point	°C	-42
Flash Point	°C	>201