

DESCRIPTION:

Rymax Styx UTTO 85W is an outstanding multifunctional hydraulic and transmission oil for tractors. Styx UTTO is suitable for tractors that need one lubricant for the hydraulic system, the transmission, differential, wet brakes and clutches. Styx UTTO is formulated from mineral base oils with special additives to improve viscometrics, it contains anti friction and extreme pressure to prevent wear and tear of metal surfaces at high revs and heavy loads. Styx UTTO is suitable for all modern tractors. Styx UTTO is also available in SAE 80W.

Styx UTTO is not an engine oil.



BENEFITS:

- Optimized clutch performance due to excellent frictional properties
- Prevents from stick-slip and the accompanied noise, all year round
- Very good shear stability
- Excellent protection against wear and corrosion.
- Very good anti-foam properties

PERFORMANCE LEVELS:

- API GL-4
- Allison C-4
- Case MS 1204
- Case MS 1206
- Case MS 1207
- Case MS 1209
- Caterpillar TO-2
- CNH MAT 3540
- Ford M2C86A/B
- John Deere J20C
- MF M1135/1143/1145
- Volvo WB101 (97303)
- Eaton M2950S
- Eaton I-280-S
- Sauer Danfoss

TYPICAL PROPERTIES

SAE	Unit	85W
Density 15 °C	Kg/m3	877
Viscosity 40 °C	cSt	74
Viscosity 100 °C	cSt	11.2
Viscosity Index		142
Pour Point	°C	-42
Flash Point	°C	>201