

DESCRIPTION:

Rymax Apollo C2 C3 5W-30 is one of the most advanced performance synthetic, ultra-low emission passenger car motor oils specially designed using the most modern chemistry, meeting mid SAPS (Sulphated Ash, Phosphorous & Sulphur) requirements. It has been exclusively developed to extend life and maintain efficiency on the after treatment devices used in the latest generation passenger cars powered by both petrol and diesel engines. It provides exceptional cleaning power and wear protection leading to superior overall performance. Rymax Apollo C2 C3 5W-30 minimizes deposit in engine and turbocharger and helps maintaining Fuel Economy. It exceeds the performance requirements of the latest low emission oil specifications from leading car manufacturers.

BENEFITS:

- Lower fuel consumption
- Fast cold start properties which results in less wear due to a stable lubricant film
- Great dispersant and detergent properties, which warrants a clean operation
- Very good lubrication film at very high working temperatures
- Excellent Anti-Wear, Anti-Foaming and Anti-Corrosion properties



PERFORMANCE LEVELS:

- ACEA C2/C3
- API SN
- BMW LL-04
- GM Dexos 2
- MB 229.31
- MB 229.51
- MB 229.52
- OV0401547
- Renault RN0700
- Renault RN0710
- VW 505.00
- VW 505.01

TYPICAL PROPERTIES

SAE	Unit	5W-30
Density 15 °C:	Kg/m ³	851
Viscosity 40 °C	cSt	66.2
Viscosity 100 °C	cSt	11.8
Viscosity Index		176
Pour Point	°C	-39
Flash Point	°C	>201