

DESCRIPTION:

Rymax Apollo C3 5W-30 is an advanced performance synthetic, ultra-low emission passenger car motor oil specially designed using the most modern additive chemistry, meeting mid SAPS (Sulphated Ash, Phosphorous & Sulphur) requirements. It has been exclusively developed to extend life and maintain efficiency of the after treatment devices used in the latest generation passenger cars powered by both petrol and diesel engines. It exceeds the performance requirements of the latest low emission oil specifications of leading car manufacturers like Daimler, Chrysler and BMW. Rymax Apollo C3 5W-30 gives good protection of the catalytic converter, ensures cleaner combustion, enhanced fuel economy and low emission levels. Special additives keep the oil and engine parts free from sludge and deposits.



BENEFITS:

- Lower fuel consumption
- Fast cold start properties which results in less wear due to a stable lubricant film
- Great dispersant and detergent properties, which warrants a clean operation
- Very good lubrication film at very high working temperatures
- Excellent Anti-Wear, Anti-Foaming and Anti-Corrosion properties

PERFORMANCE LEVELS:

- ACEA C3
- API SN/CF
- BMW LL-04
- GM Dexos 2
- GM-LL-A-025
- GM-LL-B-025
- MB 229.51
- MB 229.52
- MB 229.31
- OV0401547
- VW 502.00
- VW 505.00
- VW 505.01

TYPICAL PROPERTIES

SAE	Unit	5W-30
Density 15 °C:	Kg/m3	850
Viscosity 40 °C	cSt	69
Viscosity 100 °C	cSt	11.9
Viscosity Index		170
Pour Point	°C	-39
Flash Point	°C	>201