

DESCRIPTION:

Rymax Apollo C3 5W-40 is an advanced performance synthetic, ultra-low emission passenger car motor oil specially designed using most modern additive chemistry meeting mid SAPS (Sulphated Ash, Phosphorous & Sulphur) requirements. It has been exclusively developed to extend life and maintain efficiency of the after treatment devices used in the latest generation passenger cars powered by both gasoline and diesel engines. It exceeds the performance requirements of latest low emission oil specifications leading car manufacturers like Daimler, Chrysler and BMW. This product has been developed mainly for VAG group (Volkswagen, Audi , Seat and Skoda) wherein they are also suitable for the VW diesel engines.



BENEFITS:

- Lower fuel consumption
- Fast cold start properties which results in less wear due to a stable lubricant film
- Great dispersant and detergent properties, which warrants a clean operation
- Very good lubrication film at very high working temperatures
- Very good Anti-Wear, Anti-Corrosion and Anti-Foam properties

PERFORMANCE LEVELS:

- ACEA C3
- API SN/CF
- BMW LL-04
- Ford WSS-M2C917-A
- GM Dexos 2
- MB 229.31
- MB 226.5
- Porsche A40
- Renault RN 0700
- Renault RN 0710
- VW 502.00
- VW 505.00
- VW 505.01

TYPICAL PROPERTIES

SAE	Unit	5W-40
Density 15 °C:	Kg/m ³	850
Viscosity 40 °C	cSt	85
Viscosity 100 °C	cSt	14.1
Viscosity Index		172
Pour Point	°C	-39
Flash Point	°C	>201