

DESCRIPTION:

Rymax Apollo FE 5W-30 is a full synthetic engine oil for petrol, LPG and light diesel engines with or without turbos and catalytic converter where a fuel economy oil is recommended. It has been developed with special additives, which provide optimal protection during extended drain intervals. Apollo FE family contains of four fully synthetic blends; SAE 0W-20/0W-30/5W-20/5W-30. Apollo FE ensures cleaner combustion, enhanced Fuel Economy (M111 test has shown over 3% of fuel saving) and low emission levels. Special additives keep the oil and engine parts free from sludge and deposits. It guarantees rapid and stable lubrication and high thermal stability under heavy duty conditions in a broad temperature range. It allows long drain intervals (upto 30000 km) for the latest models of Jaguar and Ford.



BENEFITS:

- Lower fuel consumption
- Fast cold start properties which results in less wear due to a stable lubricant film
- Great dispersant and detergent properties, which warrants a clean operation
- Very good lubrication film at very high working temperatures
- Very good anti-wear, anti-corrosion and anti-foam properties.

PERFORMANCE LEVELS:

- API SN
- ACEA A5/B5
- Ford WSS-M2C913-D
- Ford WSS-M2C913-C
- STJLR.03.5003
- Renault RN0700

TYPICAL PROPERTIES

| SAE | Unit | 5W-30 |
|------------------|-------------------|-------|
| Density 15 °C: | Kg/m ³ | 849 |
| Viscosity 40 °C | cSt | 54 |
| Viscosity 100 °C | cSt | 9.7 |
| Viscosity Index | | 167 |
| Pour Point | °C | -46 |
| Flash Point | °C | >201 |