

DESCRIPTION:

Rymax Apollo FE Xxtra 0W-20 is a fully synthetic engine oil designed for passenger cars, vans, and SUVs with or without turbochargers and after-treatment systems. It is suitable for petrol, diesel, hybrid, and engines running on LPG, CNG, biodiesel (B10), and ethanol (E85). Apollo FE Xxtra 0W-20 meets the requirements of many American, Asian, and European vehicles, including those that comply with Euro 6 emission standards. For applications involving frequent short trips or heavy loads, such as taxis or delivery vehicles, shorter service intervals are advised. It is also suitable for use in Fiat engines requiring Fiat 9.55535-DM1 or DSX performance levels.



BENEFITS:

- Lower fuel consumption
- Fast cold start properties which results in less wear due to a stable lubricant film
- Minimizes LSPI in turbocharged petrol engines.
- Compatible with a wide range of engines and fuels.
- Very good anti-wear, anti-corrosion and anti-foam properties

PERFORMANCE LEVELS:

- API SQ
- API SP
- API SP-RC
- ILSAC GF-7A
- ILSAC GF-6A
- ACEA C6
- ACEA C5
- BMW Longlife 17FE+
- BMW Longlife 14FE+
- Chrysler MS-12145
- Ford WSS-M2C947-B1
- Ford WSS-M2C962-A1
- Fiat 9.55535-GSX
- Jaguar Land Rover STJLR.03.5006
- Jaguar Land Rover STJLR.51.5122
- MB 229.72
- MB 229.71
- OV 040 1547 - A20
- Volvo VCC C6SP

TYPICAL PROPERTIES

SAE	Unit	0W-20
Density 15 °C	Kg/m ³	842
Viscosity 40 °C	cSt	41.8
Viscosity 100 °C	cSt	8.3
Viscosity Index		179
Pour Point	°C	-45
Flash Point	°C	225