



TECHNICAL DATA SHEET

APOLLO FE-F 0W-30

Full Synthetic Fuel Economy Engine Oil

DESCRIPTION:

Rymax Apollo FE-F 0W-30 is a fully synthetic ultra-high performance oil for the use in petrol and diesel engines in passenger cars, especially designed for the most recent Ford diesel engines. Rymax Apollo FE-F 0W-30 fulfils the requirements of Ford WSS-M2C950-A. It is also recommended for vehicles for which an engine oil meeting ACEA C2 with the viscosity grade 0W-30 is prescribed.



BENEFITS:

- Lower fuel consumption
- Fast cold start properties which results in less wear due to a stable lubricant film
- Great dispersant and detergent properties, which warrants a clean operation
- Very good lubrication film at very high working temperatures
- Very good anti-wear, anti-corrosion and anti-foam properties

PERFORMANCE LEVELS:

- ACEA C2
- Ford WSS M2C-950A
- STJLR 03.5007
- PSA B71 2312

TYPICAL PROPERTIES

SAE	Unit	0W-30
Density 15 °C:	Kg/m ³	840
Viscosity 40 °C	cSt	45
Viscosity 100 °C	cSt	9.5
Viscosity Index		202
Pour Point	°C	-48
Flash Point	°C	>201



RYMAX LUBRICANTS B.V. Delweg 8
The Netherlands 6902 PJ Zevenaar

T +31 (0) 316 740 856 E info@rymax-lubricants.com
W www.rymax-lubricants.com

[WWW.FACEBOOK.COM/RYMAXLUBRICANTS](https://www.facebook.com/RYMAXLUBRICANTS)
 [WWW.INSTAGRAM.COM/RYMAXLUBRICANTS](https://www.instagram.com/RYMAXLUBRICANTS)

All performance data on this Technical Data Sheet are indicative only and can vary during production

LUB003029

Version Number: 3

Date:
01-07-2023