



TECHNICAL DATA SHEET

APOLLO LL 0W-20

Full Synthetic Fuel Economy Engine Oil

DESCRIPTION:

Rymax Apollo LL SAE 0W-20 is a full synthetic fuel saving long life oil (PAO based) based for use in petrol- and diesel engines of passenger cars and light vans where a VAG norm 508.00/509.00 has been prescribed.

Remark:

This product is not backwards compatible with older vehicles that require the VW 504 00/507 00 specification.



BENEFITS:

- Exceptional good low temperature properties
- Excellent protection to wear by cold start
- Very high thermal- and oxidation stability
- Excellent resistance against foaming, corrosion and wear
- High dispersancy and detergency level
- High viscosity index
- Extended oil drain interval
- Improved fuel economy

PERFORMANCE LEVELS:

- API SP
- VW 508.00
- VW 509.00
- ACEA C6
- ACEA C5
- API SN Plus
- ILSAC GF-6
- Ford WSS-M2C956-A1

TYPICAL PROPERTIES

Colour	Unit	Green
Density 15 °C	Kg/m ³	835
Viscosity 40 °C	cSt	41
Viscosity 100 °C	cSt	7.8
Viscosity Index		170
Pour Point	°C	-42
Flash Point	°C	>201



RYMAX LUBRICANTS B.V.

The Netherlands

Delweg 8
6902 PJ Zevenaar

T +31 (0) 316 740 856

E info@rymax-lubricants.com

W www.rymax-lubricants.com

www.facebook.com/RYMAXLUBRICANTS

www.instagram.com/RYMAXLUBRICANTS

All performance data on this Technical Data Sheet are indicative only and can vary during production

LUB003024

Version Number: 3

Date:
01-07-2023