

DESCRIPTION:

Rymax Apollo VV 0W-20 is a fully synthetic fuel economy oil for gasoline and diesel engines in passenger cars. Apollo VV 0W-20 is intended for the new Volvo Engine Architecture (VEA engines) technology. Due to the usage of special additives all parts are kept free from sludge, dirt and deposits. Apollo VV 0W-20 offers extra fuel saving properties and allows long drain intervals (up to 30.000 km) for the latest models of Volvo. To meet the requirements of the requested fuel economy performance of the Volvo VCC RBS0-2AE specification the Apollo VV 0W-20 has a HTHS below 2.9cP. Rymax Apollo VV is also available in SAE 0W-30

Apollo VV 0W-20 is also applicable for vehicles for which a fuel economy to ACEA A1/B1 is prescribed.



PERFORMANCE LEVELS:

- ACEA C5
- API SN
- Volvo VCC RBS0-2AE

BENEFITS:

- Fast cold start properties which results in less wear due to a stable lubricant film
- Great dispersant and detergent properties, which warrants a clean operation
- Very good lubrication film at very high working temperatures
- Very good anti-wear, anti-corrosion and anti-foam properties

TYPICAL PROPERTIES

SAE	Unit	0W-20
Density 15 °C:	Kg/m3	842
Viscosity 40 °C	cSt	47
Viscosity 100 °C	cSt	9
Viscosity Index		176
Pour Point	°C	-45
Flash Point	°C	>201