

DESCRIPTION:

Rymax Apollo VV 0W-30 is a long-life, full saps technology, fully synthetic based oil formulation. Apollo VV 0W-30 has is applicable in modern Euro-4 to Euro 6 engines, diesel or gasoline, naturally aspirated or turbocharged, indirect or direct injection, requiring a SAE 0W-30 with ACEA A5/B5 and API SL specifications. Apollo VV 0W-30 enables the engine to perform under all operating conditions due to its special additive package. Rymax Apollo VV is also available in SAE 0W-20. This product is specially applicable Volvo engines.

Apollo VV 0W-30 provides excellent performance in piston cleanliness, in reducing sludge formation and in keeping the turbocharger clean. Due to unique formulation, the oil has a low evaporation tendency resulting in minimizing oil consumption.

BENEFITS:

- Fast cold start properties which results in less wear due to a stable lubricant film
- Great dispersant and detergent properties, which warrants a clean operation
- Very good lubrication film at very high working temperatures
- Very good anti-wear, anti-corrosion and anti-foam properties



PERFORMANCE LEVELS:

- ACEA A5/B5
- API SL/CF
- Volvo VCC 95200377

TYPICAL PROPERTIES

SAE	Unit	0W-30
Density 15 °C:	Kg/m3	843
Viscosity 40 °C	cSt	53.2
Viscosity 100 °C	cSt	10
Viscosity Index		178
Pour Point	°C	-45
Flash Point	°C	>201