



TECHNICAL DATA SHEET

HELIOS XR 20W-50

Engine Oil

DESCRIPTION:

Rymax Helios XR 20W-50 is one of the Helios grades from our all-season lubricants range for petrol, LPG as well as diesel engines for which the use of an API SG/CF-4 is recommended.

BENEFITS:

- Excellent detergency and dispersancy providing optimal cleanliness
- Excellent protection against black sludge in engines
- Low oil consumption ensuring long life-time
- Suitable for use for older cars as well as running-in engines



PERFORMANCE LEVELS:

- API SG/CF-4
- MIL-L-46152E/2104D

TYPICAL PROPERTIES

SAE	Unit	20W-50
Density 15 °C:	Kg/m3	878
Viscosity 40 °C	cSt	147
Viscosity 100 °C	cSt	17.6
Viscosity Index		133
Pour Point	°C	-30
Flash Point	°C	>201



RYMAX LUBRICANTS B.V. Delweg 8
The Netherlands 6902 PJ Zevenaar

T +31 (0) 316 740 856

E info@rymax-lubricants.com

W www.rymax-lubricants.com



[WWW.FACEBOOK.COM/RYMAXLUBRICANTS](https://www.facebook.com/RYMAXLUBRICANTS)



[WWW.INSTAGRAM.COM/RYMAXLUBRICANTS](https://www.instagram.com/RYMAXLUBRICANTS)

All performance data on this Technical Data Sheet are indicative only and can vary during production

LUB002013

Version Number: 3

Date:
01-07-2023