

TECHNICAL DATA SHEET

HELIOS XT 20W-50

Engine Oil

DESCRIPTION:

Rymax Helios XT 20W-50 is one of the two products in the Helios XT Range. This is a high quality mineral engine oil. The Rymax Helios XT range consist of two mineral blends: 15W-40 and 20W-50. They provide excellent lubrication for passenger cars and light-duty vehicles with or without turbocharger, for petrol, diesel or LPG engines. The mineral oils are formulated with high quality refined mineral base stocks, combined with very good performance additive technologies. These lubricants offer excellent wear protection for all the parts of the engine.



BENEFITS:

- Exceptional thermal- and shear stable product, maintaining its viscosity during service life
- Low volatility
- · Excellent resistance against wear, corrosion and foaming
- Very good detergent and dispersancy level
- Optimal low temperature properties to provide easy starting and instant lubrication under all conditions

PERFORMANCE LEVELS:

- ACEA A3/B3
- API SL/CF
- MB 229.1
- VW 501.01
- VW 505.00

TYPICAL PROPERTIES

SAE	Unit	20W-50
Density 15 °C:	Kg/m3	881
Viscosity 40 °C	cSt	153
Viscosity 100 °C	cSt	17.5
Viscosity Index		125
Pour Point	°C	-30
Flash Point	°C	>201



RYMAX LUBRICANTS B.V. Delweg 8

Delweg B 6902 PJ Zevenaar T +31 (0) 316 740 856

E info@rymax-lubricants.com W www.rymax-lubricants.com

Version Number: 3