

## **TECHNICAL DATA SHEET**

# **POSIDON 10W-40**

**Synthetic Engine Oil** 

#### **DESCRIPTION:**

Rymax Posidon 10W-40 is a synthetic engine oil that is developed to meet the most modern requirements of passenger car manufacturers. The Rymax Posidon family comes in two synthetic blends; 10W-30 and 10W-40, and in three fully synthetic blends; 5W-30, 5W- 40 and 5W-50.

This product is unsuitable for diesel engines with Diesel Particulate filter (DPF)



#### **BENEFITS:**

- Low temperature properties to ensure smoother cold start
- Excellent thermal and oxidation stability
- High dispersancy and detergency level
- Excellent Anti-Wear, Anti-Foaming and Anti-Corrosion properties
- Lower fuel consumption

#### **PERFORMANCE LEVELS:**

- ACEA A3/B3
- API SL/CF
- MB 229.1
- VW 501.01
- VW 505.00

### **TYPICAL PROPERTIES**

SAE	Unit	10W-40
Density 15 °C:	Kg/m3	857
Viscosity 40 °C	cSt	91.2
Viscosity 100 °C	cSt	14.4
Viscosity Index		164
Pour Point	°C	-39
Flash Point	°C	>201



RYMAX LUBRICANTS B.V. Delweg B

Delweg 8 6902 PJ Zevenaar T +31 (0) 316 740 856

E info@rymax-lubricants.com W www.rymax-lubricants.com WWW.FACEBOOK.COM/RYMAXLUBRICANTS
WWW.INSTAGRAM.COM/RYMAXLUBRICANTS