

# **TECHNICAL DATA SHEET**

# **POSIDON 5W-40**

**Full Synthetic Engine Oil** 

### **DESCRIPTION:**

Rymax Posidon 5W-40 is a fully synthetic engine oil that is developed to meet the most modern requirements of passenger car manufacturers. The Rymax Posidon family comes in two synthetic blends; 10W-30 and 10W-40, and in three fully synthetic blends; 5W-30, 5W-40 and 5W-50.

This product is unsuitable for diesel engines with Diesel Particulate filter (DPF)



### **BENEFITS:**

- Low temperature properties to ensure smoother cold start
- Excellent thermal and oxidation stability
- High dispersancy and detergency level
- Excellent Anti-Wear, Anti-Foaming and Anti-Corrosion properties
- Lower fuel consumption

#### **PERFORMANCE LEVELS:**

- ACEA A3/B4
- API SN/CF
- MB 229.3
- GM-LL-B-025
- Porsche A40
- PSA B71 2296
- Renault RN 0700
- Renault RN 0710
- VW 502.00
- VW 505.00

## **TYPICAL PROPERTIES**

| SAE              | Unit  | 5W-40 |
|------------------|-------|-------|
| Density 15 °C:   | Kg/m3 | 850   |
| Viscosity 40 °C  | cSt   | 92.1  |
| Viscosity 100 °C | cSt   | 14.8  |
| Viscosity Index  |       | 168   |
| Pour Point       | °C    | -36   |
| Flash Point      | °C    | >201  |



RYMAX LUBRICANTS B.V. Delweg B

Delweg B 6902 PJ Zevenaar T +31 (0) 316 740 856

E info@rymax-lubricants.com W www.rymax-lubricants.com

COM P WWW.INSTAGRAM.C

Version Number: 3

WWW.FACEBOOK.COM/RYMAXLUBRICANTS
 WWW.INSTAGRAM.COM/RYMAXLUBRICANTS