

### DESCRIPTION:

Posidon C3 LL SAE 5W-30 is a fully synthetic engine oil suitable for use in gasoline-, LPG- and diesel engines, with and without turbo, and also those equipped with an after treatment system (diesel particle filter for Euro IV). This oil is developed in particular for passenger cars and vans manufactured by the VAG-group (Volkswagen, Audi, SEAT, Skoda). Posidon C3 LL is developed with a special additive technology, which contains less phosphorus, sulphur and sulphated ash, to prevent the after treatment system (particle filter and catalysts) from failure. Rymax Posidon C3 LL has been developed to meet the VW specifications 504.00 and 507.00, MB 229.51 and BMW LL-04. This engine oil is not suitable for R5 and V10 diesel engines.



### BENEFITS:

- Low fuel consumption
- High viscosity Index and a high resistance against shearing
- Fast cold start properties which results in less wear due to a stable lubricant film
- Great dispersant and detergent properties, which warrants a clean operation
- Very good anti-wear, anti-corrosion and anti-foam properties

### PERFORMANCE LEVELS:

- ACEA C3
- API SN
- BMW LL-04
- MB 229.51
- Porsche C30
- VW 504.00
- VW 507.00

### TYPICAL PROPERTIES

SAE	Unit	5W-30
Density 15 °C:	Kg/m <sup>3</sup>	848
Viscosity 40 °C	cSt	72.1
Viscosity 100 °C	cSt	12.2
Viscosity Index		168
Pour Point	°C	-39
Flash Point	°C	>201