

TECHNICAL DATA SHEET

POSIDON XR 10W-40

Synthetic Engine Oil

DESCRIPTION:

Rymax Posidon XR 10W-40 is a synthetic motor oil formulated from finest quality synthetic base stocks and state-of-the-art additive technology. Our Posidon XR range consists out of semi synthetic blend, SAE 10W-40 and two full synthetic blends; SAE 0W-40/5W-40. Posidon XR has been specially developed for all modern turbocharged, high output petrol and diesel engines of passenger cars, SUVs, light vans and trucks. It has been designed to deliver a long service life and minimizes deposits in engine and turbocharger to ensure rated engine power and torque.

Recommended for all modern vehicles including high performance, turbocharged, multi valve, direct injection gasoline and diesel engines of passenger cars.



- Low Temperature properties to ensure smoother cold start
- Excellent thermal and oxidation stability
- · High dispersancy and detergency level
- Excellent anti wear, anti-foaming and anti-corrosion properties
- · High thermal and oxidation stability



PERFORMANCE LEVELS:

- ACEA A3/B4
- API SN/CF
- MB 229.1
- MB 229.3
- Renault RN 0700
- Renault RN 0710
- VW 501.01
- VW 505.00

TYPICAL PROPERTIES

SAE	Unit	10W-40
Density 15 °C:	Kg/m3	859
Viscosity 40 °C	cSt	94
Viscosity 100 °C	cSt	14.1
Viscosity Index		154
Pour Point	°C	-39
Flash Point	°C	>201



RYMAX LUBRICANTS B.V. Delweg 8

Delweg B 6902 PJ Zevenaar T +31 (0) 316 740 856

E info@rymax-lubricants.com W www.rymax-lubricants.com

nts.com 🧓 ww

WWW.FACEBOOK.COM/RYMAXLUBRICANTS

WWW.INSTAGRAM.COM/RYMAXLUBRICANTS