

TECHNICAL DATA SHEET POSIDON XR 5W-40

Full Synthetic Engine Oil

DESCRIPTION:

Rymax Posidon XR 5W-40 is a fully synthetic engine oil formulated from the best quality synthetic base stocks and state-of-the-art additive technology. Our Rymax Posidon XR range consists out of a synthetic blend: 10W-40 and two fully synthetic blends; 0W-40 and 5W-40. Posidon XR has been specially developed for all modern turbocharged, high output petrol and diesel engines of passenger cars, SUVs, light vans and trucks. Rymax Posidon XR 0W-40 has been designed to deliver a long service life and minimizes deposits in engine and turbocharger to ensure retained engine power and torque. Recommended for all modern vehicles including high performance, turbo-charged, multi-valve, direct injection petrol and diesel engines of passenger cars.



PERFORMANCE LEVELS:

- ACEA A3/B4
- API SN/CF
- BMW LL-01
- MB 229.5
- MB 226.5
- PSA B71 2296
- Renault RN 0700
- Renault RN 0710VW 502.00
- • • 502.00
- VW 505.00

BENEFITS:

- · Low temperature properties to ensure smoother cold start
- Excellent thermal and oxidation stability
- High dispersancy and detergency level
- Excellent Anti-Wear, Anti-Foaming and Anti-Corrosion properties
- · High thermal and oxidation stability

TYPICAL PROPERTIES

SAE	Unit	5W-40
Density 15 °C:	Kg/m3	852
Viscosity 40 °C	cSt	85
Viscosity 100 °C	cSt	14.4
Viscosity Index		177
Pour Point	°C	-39
Flash Point	°C	>201



RYMAX LUBRICANTS B.V.
Delweg B
T + 31 (0) 316 740 856
E info@rymax-lubricants.com
Image: Comparison of the comparison o

Date: 01-07-2023