

### DESCRIPTION:

Rymax Dione G-12++ Ready-to-use is a modern, easy to use coolant based on mono ethylene glycol developed specifically to meet the latest standards from Volkswagen (VW TL 774G). The product is free of nitrites, amines, phosphates and based on SOAT technology (Silicated Organic Acid Technology) for long periods of protection of all metal alloys. Rymax Dione G-12++ Ready-to-use is suitable for use in both petrol and diesel engines and has been introduced to meet the demands of OEM's who favour this combination of organic & silicate technology. This coolant can be used in models from year 2007 and is backward compatible with the G11, G12 and G12 + standards.



### HOW TO USE:

Rymax Dione G12++ Ready-to-use coolant and antifreeze is already pre-mixed with water and is ready to use, providing a permanent and guaranteed protection against freezing and excellent cooling.

### PERFORMANCE LEVELS:

- AFNOR NF R15-601
- ASTM D 3306
- ASTM D 4985
- SAE J 1034
- BS 6580
- FFV Heft R443
- CUNA NC 956-16
- UNE 26361-88
- JIS K2234
- NATO S 759 KSM 2142
- EMPA
- E/L 1415C (MIL Italy)
- Audi TL 774 G
- Bentley TL 774 G
- Bugatti TL 774 G
- Lamborghini TL 774 G
- Porsche
- Scania
- Seat TL 774 G
- Skoda TL 774 G
- Volkswagen VAG TL 774 G

### TYPICAL PROPERTIES

	Unit	50/50
Density 15 °C:	Kg/m3	1070
Colour		Pink
pH		8.2
Freezing point	°C	-37
Boiling point	°C	110
Water content	%	3