



TECHNICAL DATA SHEET

DIONE TC READY-TO-USE

Tropical Ready-to-use Antifreeze and Engine Coolant

DESCRIPTION:

Rymax Dione TC Ready-to-use is a modern, easy to use coolant made with organic acid technology (OAT). This tropical coolant is free of nitrites, amines, silicates, phosphates, or borates, and is developed to protect all common metals and alloys used in internal combustion engine cooling systems, including aluminium and steel components.

When mixed with ethylene glycol, Rymax Dione TC functions as both an engine coolant and antifreeze, offering reliable protection against corrosion and thermal degradation under a wide range of operating temperatures. It can also be used without glycol as a summer or tropical coolant, where protection against freezing is not required.

The product is green in color.



NOTE:

Dione TC Ready-to-use coolant and antifreeze is pre-mixed with water and is ready to use, providing a permanent and guaranteed protection for tropical temperatures.

TYPICAL PROPERTIES

	Unit	5/95
Density 15 °C	Kg/m3	1184
Colour		Green
pH		8.2



RYMAX B.V.
The Netherlands

Delweg 8
6902 PJ Zevenaar

T +31 (0) 316 740 856
F +31 (0) 316 740 844

E info@rymax-lubricants.com
W www.rymax-lubricants.com

f [WWW.FACEBOOK.COM/RYMAXLUBRICANTS](https://www.facebook.com/RYMAXLUBRICANTS)
@ [WWW.INSTAGRAM.COM/RYMAXLUBRICANTS](https://www.instagram.com/RYMAXLUBRICANTS)

All performance data on this Technical Data Sheet are indicative only and can vary during production

LUB002354

Version Number: 1

Date:
26-06-2025