

TECHNICAL DATA SHEET

ATEXIO +4

Full Synthetic Automatic Transmission Fluid

DESCRIPTION:

Rymax Atexio +4 ATF is a fully synthetic automatic transmission fluid (ATF) and particularly recommended for Chrysler automatic transmissions. This product is also suitable for power steering systems and hydraulic systems, where an excellent low temperature fluidity is required. This ATF meets the +4 ATF (MS-9602) service fill specification and replaces ATF+3 (MS-7176). Rymax Atexio +4 ATF is especially recommended for top-up or re-fill after repair or revision of Chrysler automatic transmissions where an ATF +3 and ATF +4 are prescribed.



BENEFITS:

- Excellent thermal and oxidative stability
- Excellent protection from foaming, wear and corrosion
- Smooth and lasting shift feel even after extensive usage
- · Contribution to fuel saving
- High viscosity index ensuring good lubrication in both high and low temperatures

PERFORMANCE LEVELS:

- Mopar ATF +4 (MS-9602)
- Mopar ATF +3 (MS 7176E)
- Mopar ATF +2 (MS 7176D)
- Mopar ATF+ (MS 7176)
- MS-9602

TYPICAL PROPERTIES

Colour	Unit	Red
Density 15 °C	Kg/m3	846
Viscosity 40 °C	cSt	36
Viscosity 100 °C	cSt	7.2
Viscosity Index		180
Pour Point	°C	-48
Flash Point	°C	197



RYMAX LUBRICANTS B.V. Delweg B

Delweg 8 6902 PJ Zevenaar T +31 (0) 316 740 856

E info@rymax-lubricants.com W www.rymax-lubricants.com

