

DESCRIPTION:

Rymax Atezio DCT is a fully synthetic long life fluid especially formulated (and only suitable for) double clutch transmissions (DCT) in vehicles from the VAG (Volkswagen Audi) group. This transmission system, also known as DSG (Direct-Shift Gearbox), is developed for racing applications and is modified for use in passenger cars from Volkswagen, Audi, SEAT and Skoda. Rymax Atezio DCT is composed in such a way that it remains its unique characteristics even under the most severe circumstances. These circumstances could vary from intensive use (high rpms) and severe winter conditions.



BENEFITS:

- Excellent thermal and oxidative stability
- Excellent anti-wear, anti-rust and anti-corrosive properties
- Very low pour point which leads to easy cold start
- Compatibility with all type of seal materials
- High viscosity index ensuring good lubrication in both high and low temperatures

PERFORMANCE LEVELS:

BMW:

- BMW Drivelogic 7-speed (Getrag)/DCTF-1
- BMW DCTF-1+
- BMW DCTF-2
- BMW 6-speed DCT
- BMW 83 22 2 167 666/MTF LT-5

Borg Warner

Bugatti Veyron

BYD:

- BYD DCTs, Q/BYD-A1909.0058-2013

Castrol:

- Castrol BOT 341
- Castrol BOT 351 C4
- Castrol BOT 450

Changan:

- Changan DCTF

Chrysler:

- Chrysler 68044345 EA & GA
- Chrysler Powershift 6-speed (Getrag)

Eaton:

- Eaton PS-278

Porsche:

- Porsche 999.917.080.01
- 7-speed PDK

Renault:

- Renault EDC 6-speed (Getrag)
- Renault EDC-7,
- Renault DC4 (BOT 450)
- Renault DW5
- Renault DW6

Volvo:

- Volvo Powershift 6-speed (GFT)/1161838/1161839

VW:

- VW G 052 182
- VW G 052 536
- VW G 055 536
- VW Audi G 052 512
- VW (Audi, Seat, Skoda) 6-speed
- VW/Audi TL 52529 (spec) / G 052 529 A2 or A6 (fluid)/DSG7 = S-Tronic 7/ 7 speed VW (Audi, Seat, Skoda)
- VW/Audi G 055 529
- VW/Audi TL 521 82 (spec) / G 052 182 A2 or A6 (fluid)
- e-Mobility Claims : VW Golf GTE DQ400E

ZF:

- ZF/Porsche Oil #999.917.080.00



TECHNICAL DATA SHEET

ATEXIO DCT

Full Synthetic Automatic Transmission Fluid

PERFORMANCE LEVELS:

Ferrari:

- Ferrari 7-speed (Getrag)/TF DCT-3

Ford:

- Ford/Nissan Powershift 6-speed (GFT) / Ford WSS-M2C936A part 1490763/1490761
- Ford WSS-M2C200-D2/ XT-11-QDC
- Ford WSS-M2C218-A1
- Ford F-DC, part KU7J M2C218AA

Geely:

- Geely 7 speed

Great Wall:

- Great Wall DCT

MB:

- MB 236.21
- MB 236.24
- MB 236.25

Mitsubishi:

- Mitsubishi TC-SST 6-speed (GFT) / MZ320065 DiaQueen SSTF-1

Peugeot/Citroen:

- Peugeot/Citroen DCS 6-speed (GFT)/9734.S2

TYPICAL PROPERTIES

Colour	Unit	Amber
Density 15 °C	Kg/m ³	849
Viscosity 40 °C	cSt	36.7
Viscosity 100 °C	cSt	6.9
Viscosity Index		174
Pour Point	°C	-48
Flash Point	°C	>201



RYMAX B.V.
The Netherlands

Delweg 8
6902 PJ Zevenaar

T +31 (0) 316 740 856
F +31 (0) 316 740 844

E info@rymax-lubricants.com
W www.rymax-lubricants.com

F www.facebook.com/RYMAXLUBRICANTS
I www.instagram.com/RYMAXLUBRICANTS

All performance data on this Technical Data Sheet are indicative only and can vary during production

LUB005109

Version Number: 4

Date:
23-12-2025