

DESCRIPTION:

Rymax Atezio III is high quality automatic transmission fluid (ATF) that is developed for OEM equipment after 1995 and older transmissions. It gives extremely long service life in the most severe operating conditions. The fluids operating range is between -45 °C and + 160 °C. Rymax Atezio III acts as an excellent hydraulic fluid and surpasses the performance of most top quality Anti-Wear hydraulic fluids or motor oils. It is also suitable for use with Sundstrand, Rexnord, Vickers and Hagglunds- Denison (except certain axial piston) hydraulic pumps. This ATF III is superior to 10W motor oils commonly used in mobile equipment hydraulic systems, because it has better cold start performance, superior materials compatibility and a greater resistance to oxidation.



BENEFITS:

- Excellent oxidative and thermal stability
- Excellent cold starting performance due to low pour point
- Compatible with all types of seals preventing sludge
- Excellent protection against wear, foam and corrosion
- Smooth shifting due to special friction modifiers

PERFORMANCE LEVELS:

- Allison C4
- Dexron III F
- Dexron III G
- Dexron III H
- CAT TO-2
- Ford Mercon
- MAN 339 Z1/Z2
- MAN 339 V1/V2
- MB 236.10
- MB 236.9
- MB 236.7
- MB 236.5
- MB 236.1
- Voith 55.6335
- Volvo 97341
- ZF 02F/03D/04D
- ZF 11A/11B/14B/16L

TYPICAL PROPERTIES

| Colour | Unit | Red |
|------------------|-------------------|------|
| Density 15 °C | Kg/m ³ | 853 |
| Viscosity 40 °C | cSt | 36 |
| Viscosity 100 °C | cSt | 7.2 |
| Viscosity Index | | 178 |
| Pour Point | °C | -48 |
| Flash Point | °C | >201 |