

DESCRIPTION:

Rymax Gevitro GL-5 85W-140 are universal mineral transmissions oils developed for hypoid gears and hub reduction in passenger cars, buses and commercial vehicles where an API GL-5 is recommended. It is also available in 80W-90. Rymax Gevitro GL-5 lubricants are formulated with paraffinic base oils and additives providing excellent protection against metal-to-metal contact of the gears under the most severe operating conditions, even under shock loads.



BENEFITS:

- Excellent protection against wear and corrosion
- Optimum extreme pressure properties, providing a superb protection against metal-to-metal contact under the toughest conditions
- Very good oxidation and thermal stability
- Excellent seal compatibility
- Splendid performance in all temperature ranges, for a perfect all-seasons coverage

PERFORMANCE LEVELS:

- API GL-5
- MIL-L-2105D
- ZF TE-ML 05A
- ZF-TE-ML 07A
- ZF-TE-ML 12E
- ZF-TE-ML 16B
- ZF-TE-ML 16C
- ZF-TE-ML 16D

TYPICAL PROPERTIES

ISO-VG	Unit	85W-140
Density 15 °C:	Kg/m ³	901
Viscosity 40 °C	cSt	380
Viscosity 100 °C	cSt	26
Viscosity Index		95
Pour Point	°C	-15
Flash Point	°C	>201