



TECHNICAL DATA SHEET

GEVITRO GL-5 HD 85W-90

Heavy Duty Gear Oil

DESCRIPTION:

Rymax Gevitro GL-5 HD 85W-90 is a high performance gear lubricant for use in heavy duty axle drives of commercial vehicles and passenger cars and is blended from high quality base oils and performance additives to provide excellent protection to gear components. Rymax Gevitro GL-5 HD's excellent extreme pressure properties impart high load-carrying capability to provide reliable protection to gear components in applications where extreme pressure and shock loading are encountered. It provides effective protection against oxidation, degradation, rust & corrosion and a long service life and low running costs. Not suitable for automatic transmissions.



BENEFITS:

- Excellent anti-wear, anti-rust and anti-corrosive properties under various operating conditions
- Minimization of sludge and deposit formation due to high oxidation stability
- Low pour point enables easy start up under low ambient temperatures
- Excellent seal compatibility
- Good anti-foam properties

PERFORMANCE LEVELS:

- API GL-5
- MAN 342 Type M1
- MAN 342 Type M2
- MB 235.6
- MIL-L-2105D
- Arvin Meritor 0-76-D
- SAE J2360
- Scania STO 1.0
- Volvo 97310
- Volvo 97316
- ZF TE-ML 05A
- ZF TE-ML 07A
- ZF TE-ML 08
- ZF TE-ML 12M
- ZF TE-ML 16B
- ZF TE-ML 16C
- ZF TE-ML 16D
- ZF TE-ML 17B
- ZF TE-ML 19B
- ZF TE-ML 21A

TYPICAL PROPERTIES

ISO-VG	Unit	85W-90
Density 15 °C:	Kg/m3	893
Viscosity 40 °C	cSt	192
Viscosity 100 °C	cSt	17.8
Viscosity Index		101
Pour Point	°C	-27
Flash Point	°C	>201



RYMAX LUBRICANTS B.V.

The Netherlands

Delweg 8

6902 PJ Zevenaar

T +31 (0) 316 740 856

E info@rymax-lubricants.com

W www.rymax-lubricants.com

All performance data on this Technical Data Sheet are indicative only and can vary during production

LUB005018

Version Number: 3

www.facebook.com/rymaxlubricants

www.instagram.com/rymaxlubricants

Date:
01-07-2023