

### DESCRIPTION:

Rymax Gevitro GL-5 LS 80W-90 is recommended for passenger cars with limited slip differentials. Rymax Gevitro GL-5 LS is a high quality, hypoid type gear oil, specifically developed for limited slip differential units fitted to modern, high performance passenger cars and off-road leisure vehicles. It can be used in limited slip differentials of European, Japanese and American built vehicles, and is equally suitable in transmissions, gear axles, steering boxes and universal joints, etc. Rymax Gevitro GL-5 LS is recommended for high performance passenger cars and sports cars frequently running at high speed and is equally suited in a wide range of applications where an EP-type gear oil is specified. It is also available in SAE 85W-140.



### BENEFITS:

- Optimizes frictional characteristics of the limited slip components
- Effective in reducing transmission noise
- Excellent load bearing characteristics
- Improved fuel economy due to good frictional properties
- Gives maximum protection of the gears, bearings and limited-slip components performance

### PERFORMANCE LEVELS:

- API GL-5
- Arvin Meritor
- MAN 342 Type M1/M2
- MIL-L-2105D
- Volvo 1273.10
- ZF TE-ML 05C
- ZF TE-ML 07A
- ZF TE-ML 08
- ZF TE-ML 12E
- ZF TE-ML 16E
- ZF TE-ML 17B
- ZF TE-ML 19B
- ZF TE-ML 21C

### TYPICAL PROPERTIES

ISO-VG	Unit	80W-90
Density 15 °C:	Kg/m <sup>3</sup>	888
Viscosity 40 °C	cSt	136
Viscosity 100 °C	cSt	14.1
Viscosity Index		105
Pour Point	°C	-33
Flash Point	°C	>201