

### DESCRIPTION:

Rymax Gevitro GL-5 LS 85W-140 is recommended for passenger cars with limited slip differentials. Rymax Gevitro GL-5 LS is a high quality, hypoid type gear oil, specifically developed for limited slip differential units fitted to modern, high performance passenger cars and off-road leisure vehicles. It can be used in limited slip differentials of European, Japanese and American built vehicles, and is equally suitable in transmissions, gear axles, steering boxes and universal joints, etc. Rymax Gevitro GL-5 LS is recommended for high performance passenger cars and sports cars frequently running at high speed and is equally suited in a wide range of applications where an EP-type gear oil is specified. It is also available in SAE 80W-90.



### BENEFITS:

- Optimizes frictional characteristics of the limited slip components
- Effective in reducing transmission noise
- Excellent load bearing characteristics
- Improved fuel economy due to good frictional properties
- Gives maximum protection of the gears, bearings and limited-slip components performance

### PERFORMANCE LEVELS:

- API GL-5
- MAN 342 Type M1
- MAN 342 Type M2
- MB 235.0
- MIL-L-2105D
- ZF TE-ML 05C
- ZF-TE-ML 12C
- ZF-TE-ML 16E

### TYPICAL PROPERTIES

ISO-VG	Unit	85W-140
Density 15 °C:	Kg/m <sup>3</sup>	903
Viscosity 40 °C	cSt	370
Viscosity 100 °C	cSt	26
Viscosity Index		92
Pour Point	°C	-20
Flash Point	°C	>201