

DESCRIPTION:

Introducing Gevitro R 75W-140, a high-quality racing gear oil engineered to fulfill the rigorous demands of racing applications, as well as light-duty and heavy-duty commercial vehicles, and off-highway equipment operating under the most extreme conditions. This fully synthetic total driveline lubricant is designed to excel in the most challenging racing scenarios. With its unique additive technology, Gevitro R allows for the use of a single lubricant across rear axles, synchronized and non-synchronized manual transmissions, simplifying maintenance and ensuring consistent performance throughout the driveline.

Formulated with premium PAO (PolyAlphaOlefin) base oil, Gevitro R delivers exceptional quality and performance. Paired with a special additive package, this gear oil offers superior lubrication, protection, and efficiency for racing applications.

Choose Gevitro R for your racing gear oil needs, and experience the benefits of a high-quality synthetic lubricant specifically tailored to meet the demanding requirements of racing, commercial vehicles, and off-highway equipment. It has been rigorously tested and proven at renowned motorsport events like the Gatebil Drift Festival and The Morocco Desert Challenge. Our R-line products are the epitome of performance and reliability.

BENEFITS:

- Exceptional thermo-oxidative stability
- Exceptional load-bearing characteristics
- Effective rust and corrosion protection
- Outstanding low-temperature fluidity
- Superior frictional properties



PERFORMANCE LEVELS:

- API GL-4
- API GL-5,
- API MT-1
- Arvin Meritor 0-76-N
- DAF
- IVECO
- MAN M3343S
- MAN 341 Type E3
- MAN 341 Type Z2
- MAN 342 Type M3
- MB 235.8
- MIL-PRF-2105E
- Renault B0032/2 annex 3
- SAE J2360
- Scania STO 1:0
- ZF TE-ML
02B/05B/07A/12B/12L/12N/16F/
17B/19C/21B

TYPICAL PROPERTIES

SAE	Unit	75W-140
Density 15 °C:	Kg/m3	869
Viscosity 40 °C	cSt	196
Viscosity 100 °C	cSt	28
Viscosity Index		182
Pour Point	°C	-52
Flash Point	°C	>201