

DESCRIPTION:

Rymax Gevitro TDL 80W-90 is a premium Total Drive Line gear oil suitable for use where an API GL-3, 4 or 5 is recommended. It can be used in conventional and modern gear boxes and rear axle differentials of passenger cars, trucks or buses, under lighter or very heavy duty conditions. Rymax Gevitro TDL products allow the use of one single lubricant in rear axles, synchronised and non-synchronized manual transmissions and therefore helps the rationalisation and efficiency of products used in daily operation. This lubricant is not suitable for use in Limited Slip applications



BENEFITS:

- Fully compatible with synchromesh gearboxes
- Excellent shifting performance in all temperature conditions, for a perfect all-seasons coverage
- Optimum resistance against wear, corrosion and foam building
- Very high oxidation and thermal stability
- Improved Fuel Economy due to excellent frictional properties

PERFORMANCE LEVELS:

- API GL-4
- API GL-5
- API MT-1
- Arvin Meritor 076-N
- DAF
- IVECO
- Mack GO-J
- MAN 341 Type E2
- MAN 241 Type Z2
- MAN 342 Type M2
- MB 235.0
- MIL-PRF-2105E
- Renault B0032/2
- SAE J2360
- Scania STO 1:0
- Volvo 97310
- ZF TE-ML 02B
- ZF TE-ML 05A
- ZF TE-ML 07A
- ZF TE-ML 08
- ZF TE-ML 12E
- ZF TE-ML 12L
- ZF TE-ML 12M
- ZF TE-ML 16B
- ZF TE-ML 16C
- ZF TE-ML 16D
- ZF TE-ML 17B
- ZF TE-ML 19B
- ZF TE-ML 21A

TYPICAL PROPERTIES

ISO-VG	Unit	80W-90
Density 15 °C:	Kg/m ³	894
Viscosity 40 °C	cSt	147
Viscosity 100 °C	cSt	15.1
Viscosity Index		103
Pour Point	°C	-30
Flash Point	°C	>201