

TECHNICAL DATA SHEET

GEVITRO TO-4 30

Transmission Fluid

DESCRIPTION:

Rymax Gevitro TO-4 is a high-performance drive line oil designed for powershift transmissions, final drives and wet brakes for highly demanding offroad equipment such as earthmoving, mine logging, road transport and agricultural applications. Rymax Gevitro TO-4 is made of top quality mineral oils and performance additives designed to fulfil the performance requirements of Caterpillar TO-4, ZF Torque converter transmissions, Komatsu powershift transmissions and Allison C-4 Automatic Transmissions. It is also available in SAE 10W/50.



BENEFITS:

- Improved oxidative and thermal stability, to give extra protection of metal surfaces against scuffing and wear
- Excellent friction properties to avoid slippage of clutches and ensure smoother operation of transmissions and brakes
- Good protection against rust and corrosion for precision equipment operating in wet environment
- Excellent compatibility with all common seal, O-rings, clutch and packing materials to avoid leakages and downtime
- Excellent dispersancy and detergency

PERFORMANCE LEVELS:

- Allison C4
- API CF/CF-2
- CAT TO-4
- **DANA Powershift transmissions**
- Komatsu KES 07.868.1
- Komatsu Dresser
- ZF TE-ML 03C
- ZF TE-ML 07F

TYPICAL PROPERTIES

ISO-VG	Unit	30
Density 15 °C:	Kg/m3	882
Viscosity 40 °C	cSt	92
Viscosity 100 °C	cSt	10.9
Viscosity Index		103
Pour Point	°C	-24
Flash Point	°C	>201



RYMAX LUBRICANTS B.V. Delweg 8

6902 PJ Zevenaar

T +31 (0) 316 740 856

E info@rymax-lubricants.com

WWW.FACEBOOK.COM/RYMAXLUBRICANTS W www.rymax-lubricants.com

Version Number: 3

WWW.INSTAGRAM.COM/RYMAXLUBRICANTS