TECHNICAL DATA SHEET



CALDAX 3

Calcium Grease

DESCRIPTION:

Rymax Caldax 3 is a hydrated calcium thickened lubricating grease based on mineral oil. The grease contains antioxidants. The calcium thickener makes the product highly water resistant. Together with the stiff consistency, the grease acts as a seal as well as a lubricant. Rymax Caldax 3 is a high quality grease that is suitable for lubrication of marine applications and excels in various wet environments and conditions.

BENEFITS:

- · Good mechanical stability
- Ability to act as both seal and lubricant
- Excellent sea and fresh water resistance



SPECIFICATIONS:

- ISO 6743 ISO-L-XBAAA3
- DIN 51502 K3C-25

TYPICAL PROPERTIES

| Thickener | | Calcium |
|-----------------------------|--------|-----------------------------|
| Base Fluid | | Mineral Oil |
| Texture | | Hydrated |
| Colour | Visual | Beige |
| NLGI Grade | | 3 |
| Dropping point | °C | >90 |
| Base oil viscosity at 40°C | mm2/s | 110 |
| Base oil viscosity at 100°C | mm2/s | 12 |
| 4 Ball Weld load | Ν | 2000 |
| Penetration 60 Strokes | | 220-250 |
| Temperature Range | °C | -25°C to +60°C (Max +80 °C) |



 RYMAX LUBRICANTS B.V.
 Delweg B
 T +31 (0) 316 740 856

 The Netherlands
 6902 PJ Zevenaar

B56 E info@rymax-lubricants.com W www.rymax-lubricants.com (7) WWW.FACEBOOK.COM/RYMAXLUBRICANTS WWW.INSTAGRAM.COM/RYMAXLUBRICANTS

All performance data on this Technical Data Sheet are indicative only and can vary during production GR0080001 Version Number: 3