

DESCRIPTION:

Rymax Calindax 2 is a lithium-calcium thickened lubricating grease based on mineral oil. The grease contains Extreme Pressure and Anti Wear additives, corrosion inhibitors and antioxidants. The thickener, together with the base oil blend, makes the product suitable for the lubrication of slow moving and heavily loaded bearings. The Rymax Calindax 2 lubricating grease has excellent adhesion and water resistance characteristics. It is suitable for heavily loaded industrial applications where water wash is problematic. The product is also suitable for heavy-duty vehicles working outdoors in wet and dirty conditions.



BENEFITS:

- Excellent water resistance
- Good load carrying capacity
- Endures high shock loads

SPECIFICATIONS:

- ISO 12924:L-XB(F)CIB2
- DIN 51502 KP2K-20

TYPICAL PROPERTIES

Thickener		Lithium Calcium
Base Fluid		Mineral Oil
Texture		Smooth
Colour	Visual	Brown
NLGI Grade		2
Dropping point	°C	>180
Base oil viscosity at 40°C	mm ² /s	660
Base oil viscosity at 100°C	mm ² /s	37
4 Ball Weld load	N	4200
Penetration 60 Strokes		265-295
Temperature Range	°C	-20 °C to 120 °C (Max + 130 °C)