



## TECHNICAL DATA SHEET

### LINDAX EP 2

Extreme Pressure & Multipurpose Lithium Grease

#### DESCRIPTION:

Rymax Lindax EP 2 is a lithium thickened lubricating grease based on virgin mineral oil. The product is a general multipurpose grease which can be used in various applications within given temperature limits. It contains Extreme Pressure additives. Rymax Lindax EP 2 can be used in both industrial and automotive applications. The grease is suitable for a wide range of plain- and rolling bearings.



#### BENEFITS:

- Good resistance to shock loads
- Wide range of use
- Good resistance to water

#### SPECIFICATIONS:

- ISO 12924: L-XC(F)CAB2
- DIN 51502: KP2K-30

#### TYPICAL PROPERTIES

Thickener		Lithium
Base Fluid		Mineral Oil
Texture		Smooth
Colour	Visual	Yellow Brown
NLGI Grade		2
Dropping point	°C	>180
Base oil viscosity at 40°C	mm <sup>2</sup> /s	90-120
Base oil viscosity at 100°C	mm <sup>2</sup> /s	11
4 Ball Weld load	N	2600
Penetration 60 Strokes		265-295
Temperature Range	°C	-30 °C to 120 °C (Max + 130 °C)



**RYMAX LUBRICANTS B.V.** Delweg 8  
The Netherlands 6902 PJ Zevenaar

T +31 (0) 316 740 856

E [info@rymax-lubricants.com](mailto:info@rymax-lubricants.com)

W [www.rymax-lubricants.com](http://www.rymax-lubricants.com)

[WWW.FACEBOOK.COM/RYMAXLUBRICANTS](https://www.facebook.com/RYMAXLUBRICANTS)

[WWW.INSTAGRAM.COM/RYMAXLUBRICANTS](https://www.instagram.com/RYMAXLUBRICANTS)

All performance data on this Technical Data Sheet are indicative only and can vary during production GR0020001 Version Number: 3

Date:  
13-11-2023