



TECHNICAL DATA SHEET

LINDAX EP 3

Extreme Pressure & Multipurpose Lithium Grease

DESCRIPTION:

Rymax Lindax EP 3 is a lithium thickened lubricating grease based on virgin mineral oil. The product is a general multipurpose grease which can be used in various applications within given temperature limits. It contains Extreme Pressure additives and corrosion inhibitors. It can be used in a wide variety of industrial and automotive applications. Rymax Lindax EP 3 grease is suitable for a large range of plain- and rolling bearings. Because of the high quality corrosion protection additives, it is suitable to be used for bearing lubrication in wet environments.



BENEFITS:

- Good resistance to shock loads
- Wide range of use
- Good resistance to water

SPECIFICATIONS:

- ISO 12924: L-XC(F)CHB3
- DIN 51502: KP3K-30

TYPICAL PROPERTIES

Thickener		Lithium
Base Fluid		Mineral Oil
Texture		Smooth
Colour	Visual	Yellow Brown
NLGI Grade		3
Dropping point	°C	>180
Base oil viscosity at 40°C	mm ² /s	110
Base oil viscosity at 100°C	mm ² /s	11
4 Ball Weld load	N	2600
Penetration 60 Strokes		220-250
Temperature Range	°C	-30°C to +120°C (Max +130°C)



RYMAX LUBRICANTS B.V. Delweg 8
The Netherlands 6902 PJ Zevenaar

T +31 (0) 316 740 856 E info@rymax-lubricants.com
W www.rymax-lubricants.com

www.facebook.com/RYMAXLUBRICANTS
www.instagram.com/RYMAXLUBRICANTS

All performance data on this Technical Data Sheet are indicative only and can vary during production GR0030001 Version Number: 3

Date:
13-11-2023