



TECHNICAL DATA SHEET

LINDAX MP 2

Multipurpose Lithium Grease

DESCRIPTION:

Rymax Lindax MP 2 is a lithium thickened lubricating grease based on virgin mineral oil. The product is a general multipurpose grease which can be used in various applications within the given operating temperature range. It can be used in a wide variety of industrial and automotive applications. Rymax Lindax MP 2 grease is suitable for a large range of plain- and rolling bearings.

BENEFITS:

- Good mechanical stability
- Good resistance to water
- Wide range of use



SPECIFICATIONS:

- ISO 12924: L-XC(F)CAA2
- DIN 51502: K2K-30

TYPICAL PROPERTIES

Thickener		Lithium
Base Fluid		Mineral Oil
Texture		Smooth
Colour	Visual	Yellow Brown
NLGI Grade		2
Dropping point	°C	>180
Base oil viscosity at 40°C	mm ² /s	90-120
Base oil viscosity at 100°C	mm ² /s	11
4 Ball Weld load	N	2000
Penetration 60 Strokes		265-295
Temperature Range	°C	-30 °C to 120 °C (Max + 130 °C)



RYMAX LUBRICANTS B.V. Delweg 8
The Netherlands 6902 PJ Zevenaar

T +31 (0) 316 740 856

E info@rymax-lubricants.com

W www.rymax-lubricants.com

[WWW.FACEBOOK.COM/RYMAXLUBRICANTS](https://www.facebook.com/RYMAXLUBRICANTS)

[WWW.INSTAGRAM.COM/RYMAXLUBRICANTS](https://www.instagram.com/RYMAXLUBRICANTS)

All performance data on this Technical Data Sheet are indicative only and can vary during production GR0060001 Version Number: 3

Date:
13-11-2023