

TECHNICAL DATA SHEET

LINDAX MP 3

Multipurpose Lithium Grease

DESCRIPTION:

Rymax Lindax MP 3 is a lithium thickened lubricating grease based on virgin mineral oil. The product is a general multipurpose grease which can be used in various applications within the given operating temperature range. Rymax Lindax MP 3 can be used in a wide variety of industrial and automotive applications. The grease is suitable for a large range of plain- and rolling bearings.



BENEFITS:

- · Good mechanical stability
- · Good resistance to water
- · Wide range of use

SPECIFICATIONS:

• ISO 12924: L-XC(F)CHA3 • DIN 51502: K3K-30

TYPICAL PROPERTIES

Thickener		Lithium
Base Fluid		Mineral Oil
Texture		Smooth
Colour	Visual	Brown
NLGI Grade		3
Dropping point	°C	>180
Base oil viscosity at 40°C	mm2/s	90-120
Base oil viscosity at 100°C	mm2/s	12
4 Ball Weld load	N	2000
Penetration 60 Strokes		220 - 250
Temperature Range	°C	-20°C to +120°C (Max + 130°C)



RYMAX LUBRICANTS B.V. Delweg 8

6902 PJ Zevenaar

T +31 (0) 316 740 856

E info@rymax-lubricants.com W www.rymax-lubricants.com WWW.FACEBOOK.COM/RYMAXLUBRICANTS

WWW.INSTAGRAM.COM/RYMAXLUBRICANTS