

DESCRIPTION:

Rymax Moldax MoS2 Xxtra 2 is a lithium thickened lubricating grease based on mineral oil. The grease contains corrosion inhibitors, Extreme Pressure additives and 3% solid lubricants. This is a general multipurpose 'Moly' grease which can be used in various applications within given temperature limits. The characteristics of this greases makes it suitable for heavily loaded applications at medium speed. It can be used in both industrial and automotive applications. Rymax Moldax MOS2 XXTRA is suitable for a wide range of plain- and rolling bearings where molybdenum disulphide provides extra protection in applications with oscillating movements. Lubricating greases with molybdenum disulphide are not suitable for rolling bearings at high speed.



BENEFITS:

- Good resistance to shock loads
- Wide range of use
- Good corrosion protection

SPECIFICATIONS:

- ISO 12924: L-XC(F)CHB2
- DIN 51502: KPF2K-30

TYPICAL PROPERTIES

Thickener		Lithium
Base Fluid		Mineral Oil
Texture		Smooth
Colour	Visual	Dark Grey
NLGI Grade		2
Dropping point	°C	>180
Base oil viscosity at 40°C	mm ² /s	90-120
Base oil viscosity at 100°C	mm ² /s	11
4 Ball Weld load	N	3200
Penetration 60 Strokes		265-295
Temperature Range	°C	-30 °C to 120 °C (Max + 130 °C)