

DESCRIPTION:

Rymax Erato is a high performance turbine oil, developed for lubricating oil circulation systems of the most modern steam- and gas-turbine installations, in which often high oil temperatures occur. Also suitable for the lubrication of hydraulic systems, compressors, gears and bearings, where contamination of lubricating oil with water is a problem.

Rymax Erato is also available in ISO VG-32/46.



BENEFITS:

- Very good oxidation stability, also at very high temperatures
- Excellent rust and corrosion protection (ferro- and non-ferro metals)
- Very good water separation
- Good anti-foam properties
- Excellent water separation capability leading to removal of excess water in the system

PERFORMANCE LEVELS:

- ASTM D4304 Type I
- ISO 8068:2006(E) L-TSA
- ISO 8068:2006(E) L-TGA
- ALSTOM HTGD 90117W
- BS 489:1999
- DIN 51515-1/2 TD/TG
- GB 11120-2011 L-TSA/L-TGA
- GEK
- 107395A/27070/28143A/32568J/46506E
- Siemens TLV 9013 05 (EP)
- Solar ES 9-224

TYPICAL PROPERTIES

ISO-VG	Unit	68
Density 15 °C:	Kg/m ³	862
Viscosity 40 °C	cSt	67
Viscosity 100 °C	cSt	9.1
Viscosity Index		113
Pour Point	°C	-20
Flash Point	°C	>213