

DESCRIPTION:

Rymax Hydra XL 10W is a high performance hydraulic oil formulated from advanced base oils and a balanced additive system designed to satisfy a wide range of heavy duty hydraulic equipment requirements. This product is specifically engineered using an effective balance of dispersants and metallic detergents combined with inhibitors to control oxidation, wear, corrosion and rust. Rymax Hydra XL SAE 10W is used in a wide range of on- and off-highway hydraulic applications. Rymax Hydra XL delivers excellent performance in a wide range of hydraulic systems and components using various multi-metal designs.

Uses:

- Hydraulic systems and components used in conjunction with equipment from leading American, European and Japanese manufacturers
- Hydraulic systems where a wide range of ambient temperatures are encountered
- Hydraulic systems containing gears and bearings where good anti-wear properties are required
- On and off-highway industries including: trucking, construction, mining, quarrying, and agriculture

BENEFITS:

- Excellent oxidation resistance at higher temperatures
- Effective low and high ambient temperature performance due to high viscosity
- Good protection to rust and corrosion
- Suitable for wet brake system

TYPICAL PROPERTIES

SAE	Unit	10W
Density 15 °C:	Kg/m ³	868
Viscosity 40 °C	cSt	35.3
Viscosity 100 °C	cSt	6
Viscosity Index		115
Pour Point	°C	-36
Flash Point	°C	220



PERFORMANCE LEVELS:

- API CF/SF
- CAT TO-2
- CCMC G2/D2
- MIL-L-2104D
- MIL-L-46152D
- MTU Type 2