

#### DESCRIPTION:

Rymax Motrax 2T FS is a supreme performance full synthetic lubricant, especially developed for high output air cooled 2-stroke gasoline engines. Its unique formulation based on synthetic base fluids and advanced performance additives ensures excellent engine protection, cleanliness and low smoke, even under extreme operating conditions.

Rymax Motrax 2T FS exceeds the latest international specifications of JASO FD, ISO-L-EGD & API TC and the requirements of leading global 2-stroke motorcycle and scooter manufacturers. Suitable for oil injection and premix lubrication systems. Follow your manufacturers recommendations for oil to fuel ratio.

#### BENEFITS:

- Excellent protection against piston seizure, engine deposit and ring sticking
- No pre-ignition and spark plug fouling due to low ash formula
- Easy miscibility with gasoline ensures a stable homogeneous mixture even at low ambient temperatures



#### PERFORMANCE LEVELS:

- API TC
- JASO FD
- Husqvarna 346/372
- ISO-L-EGD
- ISO 6743-15
- Rotax 253

#### TYPICAL PROPERTIES

SAE	Unit	TSC-3
Density 15 °C:	Kg/m <sup>3</sup>	874
Viscosity 40 °C	cSt	49.4
Viscosity 100 °C	cSt	9
Viscosity Index		165
Pour Point	°C	-51
Flash Point	°C	92