

TECHNICAL DATA SHEET

MOTRAX 2T SS

2-Stroke Synthetic Engine Oil

DESCRIPTION:

Rymax Motrax 2T SS is a premium quality semi synthetic lubricant, especially developed for high powered 2-stroke air cooled gasoline engines fitted with oilinjection or premix systems. Rymax Motrax 2T SS is formulated from premium quality synthetic base oils and unique performance additives for exceptional engine protection, cleanliness and low smoke emission. These excellent results are achieved in 2-stroke motorcycle and scooter engines, even under severe operating conditions. Suitable for both oil-injection and premix lubrication systems; follow manufacturers recommendations for oil to fuel ratio.



BENEFITS:

- Excellent protection against piston seizure, engine deposit and ring sticking
- No pre-ignition and spark plug fouling due to low ash formula
- Easy miscibility with gasoline ensures stable homogeneous mixture even at low ambient temperatures

PERFORMANCE LEVELS:

- API TC
- JASO FD
- ISO-L-EGD

TYPICAL PROPERTIES

SAE	Unit	TSC-3
Density 15 °C:	Kg/m3	869
Viscosity 40 °C	cSt	69
Viscosity 100 °C	cSt	9.9
Viscosity Index		127
Pour Point	°C	-36
Flash Point	°C	85



RYMAX LUBRICANTS B.V. Delweg 8

6902 PJ Zevenaar

T +31 (0) 316 740 856

E info@rymax-lubricants.com W www.rymax-lubricants.com

Version Number: 3

WWW.FACEBOOK.COM/RYMAXLUBRICANTS WWW.INSTAGRAM.COM/RYMAXLUBRICANTS