



TECHNICAL DATA SHEET

MOTRAX 4T FS 10W-40

4-Stroke Full Synthetic Engine Oil

DESCRIPTION:

Rymax Motrax 4T FS 10W-40 is a supreme full-synthetic performance lubricant, especially developed for high output air cooled 4-stroke gasoline engines. Its unique formulation based on synthetic base fluids and advanced performance additives ensures excellent engine protection, cleanliness and low smoke, even under extreme operating conditions. Suitable for oil-injection and premix lubrication systems. Follow your manufacturers recommendations for oil to fuel ratio.

This oil can also be applied in motorcycle transmissions where a SF, SG, SH or SL oil is prescribed/advised. Motrax 4T FS provides perfect protection to the gears and wet clutches.

Motrax 4T FS is also available in SAE 5W-40/10W-40/10W-50/10W-60/15W-50/20W-50.



PERFORMANCE LEVELS:

- API SN
- JASO MA/MA2

BENEFITS:

- Excellent protection against piston seizure, engine deposit and ring sticking
- No pre-ignition and spark plug fouling due to low ash formula
- Easy miscibility with gasoline ensures stable homogeneous mixture even at low ambient temperatures

TYPICAL PROPERTIES

SAE	Unit	10W-40
Density 15 °C:	Kg/m ³	853
Viscosity 40 °C	cSt	94
Viscosity 100 °C	cSt	14.6
Viscosity Index		162
Pour Point	°C	-39
Flash Point	°C	>201



RYMAX LUBRICANTS B.V. Delweg 8
The Netherlands 6902 PJ Zevenaar

T +31 (0) 316 740 856

E info@rymax-lubricants.com

W www.rymax-lubricants.com

f www.facebook.com/RYMAXLUBRICANTS

@ www.instagram.com/RYMAXLUBRICANTS

All performance data on this Technical Data Sheet are indicative only and can vary during production **LUB002094**

Version Number: 3

Date:
01-07-2023