

DESCRIPTION:

Rymax Motrax 4T FS 10W-60 is a supreme full-synthetic performance lubricant, especially developed for high output air cooled 4-stroke gasoline engines. Its unique formulation based on synthetic base fluids and advanced performance additives ensures excellent engine protection, cleanliness and low smoke, even under extreme operating conditions. Suitable for oil-injection and premix lubrication systems. Follow your manufacturers recommendations for oil to fuel ratio.

This oil can also be applied in motorcycle transmissions where a SF, SG, SH or SL oil is prescribed/advised. Motrax 4T FS provides perfect protection to the gears and wet clutches.

Motrax 4T FS is also available in SAE 5W-40/5W-50/10W-40/10W-50/15W-50/20W-50.



PERFORMANCE LEVELS:

- API SN
- JASO MA/MA2

BENEFITS:

- Excellent protection against piston seizure, engine deposit and ring sticking
- No pre-ignition and spark plug fouling due to low ash formula
- Easy miscibility with gasoline ensures stable homogeneous mixture even at low ambient temperatures

TYPICAL PROPERTIES

SAE	Unit	10W-60
Density 15 °C:	Kg/m ³	854
Viscosity 40 °C	cSt	172
Viscosity 100 °C	cSt	25.1
Viscosity Index		180
Pour Point	°C	-42
Flash Point	°C	>201