TECHNICAL DATA SHEET

MOTRAX 4T SS 10W-30

4-Stroke Synthetic Engine Oil

DESCRIPTION:

Rymax Motrax 4T SS 10W-30 is a 4-stroke synthetic oil for motorcycles with dry or wet clutches. The balanced additive package and carefully selected base oils guarantee excellent performances under all conditions. It provides perfect protection to the gears and wet clutches. Due to its low volatility, oil consumption will be substantially reduced. Seals are not affected by Rymax Motrax 4T. The product effectively prevents stick-slip problems in wet clutches.



BENEFITS:

- Good thermo-oxidative stability to control oil thickening during the life time and to prevent harmful deposits.
- Adapted friction properties to eliminate clutch slippage and improve drivability.
- Excellent anti-wear properties to protect vital engine and gear parts.

PERFORMANCE LEVELS:

- API SN
- JASO MA2

TYPICAL PROPERTIES

SAE	Unit	10W-30
Density 15 °C:	Kg/m3	852
Viscosity 40 °C	cSt	69.5
Viscosity 100 °C	cSt	11.8
Viscosity Index		164
Pour Point	°C	-39
Flash Point	°C	>201

RYMAX LUBRICANTS B.V.
The Netherlands
Delweg 8
6902 PJ Zevenaar
T +31 (0) 316 740 856
E info@rymax-lubricants.com
W www.rymax-lubricants.com
WWW.FACEBOOK.COM/RYMAXLUBRICANTS
WWW.INSTAGRAM.COM/RYMAXLUBRICANTS

All performance data on this Technical Data Sheet are indicative only and can vary during production