



TECHNICAL DATA SHEET

MOTRAX R 5W-50

Full Synthetic Motorcycle Racing Engine Oil

DESCRIPTION:

Rymax Motrax R 5W-50 is a high performance 4-stroke racing gasoline engine oil developed specifically to meet the special requirements of latest high performance air and water-cooled 4-stroke racing motorcycles, even with catalytic converters. It provides excellent protection to engine, gearbox and wet clutch used in 4-stroke motorcycles and ensures highest degree of reliability even under severe operating conditions and temperatures. Motrax racing oil is also available in SAE 10W-60

Motrax R is based on a mixture of synthetic PolyAlphaOlefin (PAO) and Grp III base stock in combination with ester and a special selected additive package.



BENEFITS:

- Outstanding thermo-oxidative stability
- Exceptional antiwear, antirust and anticorrosion properties
- Controlled frictional properties eliminate clutch slippage
- Increased power/ fuel economy and improves drivability
- Excellent dispersancy and detergency properties
- Excellent shear stability maintains viscosity under high temperature-high shear environment and provides improved wear protection
- Outstanding low temperature properties enable easy starting at low ambient temperatures and ensure effective lubrication and wear protection at start up
- Low volatility characteristics reduce oil consumption and hydrocarbon pollution

PERFORMANCE LEVELS:

- API SN
- JASO MA/MA2

TYPICAL PROPERTIES

SAE	Unit	5W-50
Density 15 °C:	Kg/m ³	849
Viscosity 40 °C	cSt	122
Viscosity 100 °C	cSt	19.5
Viscosity Index		182
Pour Point	°C	-48
Flash Point	°C	>201



RYMAX LUBRICANTS B.V. Delweg 8
The Netherlands 6902 PJ Zevenaar

T +31 (0) 316 740 856

E info@rymax-lubricants.com

W www.rymax-lubricants.com

WWW.FACEBOOK.COM/RYMAXLUBRICANTS

WWW.INSTAGRAM.COM/RYMAXLUBRICANTS

All performance data on this Technical Data Sheet are indicative only and can vary during production

LUB002098

Version Number: 3

Date:
01-07-2023