

### DESCRIPTION:

Rymax Chain Lube Off Road is a dry, adhesive chain lubricant formulated with PTFE, specifically engineered for application on motorbike and other chains

### How to use?

- Use on room temperature
- Shake before use.
- Apply on the place to protect or lubricate.
- Let the solvents evaporate, normally this takes approximately 5 minutes.
- Remove excess of lubricant with a cloth.
- Avoid excess of lubricant.



### BENEFITS:

- **Non-Sticky Film:** Leaves a non-sticky lubricating film on treated surfaces, minimizing dirt adhesion for a cleaner and more efficient operation.
- **PTFE Dry Lubrication:** Delivers dry lubrication that effectively lubricates, penetrates, protects, and eliminates squeaking, enhancing overall chain performance.
- **Tough Lubricating Film:** This product forms a resilient lubricating film on metal surfaces, ensuring long-lasting protection and optimal functionality.
- **Penetration Capabilities:** It excels in penetrating inaccessible areas, reaching even the most intricate parts of the chain for thorough lubrication.
- **Comprehensive Protection:** Providing a robust defense against water, moisture, salt, alkalis, and acids contributing to extended chain life.
- **Anti-Corrosion Properties:** Actively shields metal surfaces, further enhancing the durability and reliability of treated chains.

### TYPICAL PROPERTIES

Contents	Unit	400 ml
Basis		Mixture based on mineral oil and PTFE
Density	g/ml	0.82
Propellant		Propane/Butane
Colour	Visual	Colorless - Light Yellow
Application Temperature	°C	10°C to 35°C
Flash Point	°C	66
Volume organic component (VOC)	%	80%
Storage Conditions		+ 5°C to +25°C
pH		Neutral