

DESCRIPTION:

Rymax Chain Lube On Road dispenses as a foam for thorough and efficient coverage, which continues to penetrate the chain assembly as the foam subsides, forming a film of high lubricity. This film has excellent cohesion and adhesion to the metal surfaces, is tacky and is extremely water repellent.

Applications:

- Chains
- Chain driven transmissions, liable to heavy load
- Conveyors

How to use?

Before use, carefully read the directions on the packaging and act accordingly. The aerosol should have room temperature. Best processing temperature 5 to 30°C. Before use, shake the aerosol.

Apply Rymax Chain Lube On Road grease in a thin layer. During the initial flow phase, when the spray can really penetrate the treated chain, the spray has a foaming effect. Optimum lubrication is obtained after evaporation of the solvent.



BENEFITS:

- High dissolving properties
- Non conductive
- Good corrosion prevention
- To be processed like oil, with the properties of grease
- Outstanding mechanical and thermal stability
- Good adhesion
- Dilatant
- Prevents wear and sticking
- Resistant to weather influences
- Resistant to weak acids and bases
- Water-repellent
- Directed jetspray

TYPICAL PROPERTIES

Contents	Unit	400 ml
Basis		Mixture based on synthetic oils and PTFE
Density	g/ml	0.82
Propellant		Propane/Butane
Colour	Visual	Colorless-Light Yellow
Application Temperature	°C	10°C to 35°C
Flash Point	°C	66
Volume organic component (VOC)	%	80%
Storage Conditions		+5°C to +25°C
pH		Neutral