

### DESCRIPTION:

Rymax Copper Grease is a premium quality copper anti-seize and thread lubricant that may be used to prevent seizing, corrosion and galling where high temperature conditions exist. Rymax copper grease contains a high percentage of micro-fine copper flakes in a bentonite grease carrier and is fortified with high quality rust and corrosion inhibitors. The operating temperature ranges from 40°C up to + 1,100°C.

### Applications

- Brake parts
- Wheel nuts
- Pipe fittings
- Exhaust parts
- Screwed connections, which are exposed to high temperature/high friction
- Battery Poles
- Thread of Spark Plugs

### How to use?

Before use, carefully read the directions on the packaging and act accordingly. The aerosol should have room temperature. Best processing temperature 5 to 30°C. Before use, shake the aerosol. Apply copper spray. The specific lubrication property is achieved after evaporation of the solvent (approximately 1 minute).



### BENEFITS:

- High thermal stability
- High pressure resistance
- Resistant to chemicals and weather influences
- Good corrosion protection
- Good electrical conductivity
- Excellent adhesion
- Prevents wear and sticking
- Directed jetspray

### TYPICAL PROPERTIES

Contents	Unit	400 ml
Basis		EP Grease and small copper
Density	g/ml	0.740
Propellant		Butane/propane
Colour	Visual	Copper
Vapor Pressure at 20 °C	Bar	3 to 4
Temperature Resistant	°C	– 40°C to + 1,100°C
Volume organic component (VOC)	%	75
Yield	g/sec	1.26