

DESCRIPTION:

Rymax Notus A-40 is a high quality effective universal spray and can be used as lubricant, rust remover, contact spray, anti corrosion and tool cleaner. Rymax Notus A-40 is used for; fastening tools, screwed connections rails, gear wheels chains, locking garden tools and for fastenering (screw, bolt and nuts) reels.

Applications

- Fastenings Tools
- Screwed connections Rails
- Gear wheels Chains
- Locks Garden tools
- Fasteners (screws, bolts etc) Reels

How to use?

Before use, carefully read the directions on the packaging and act accordingly. The aerosol should have room temperature. Best processing temperature 5 to 30°C.

- Surfaces must be cleaned, degreased, and dry.
- Shake the can well before use.
- Spray the product at a distance of approximately 20 cm from the object.
- Apply the spray as required.
- Switch electric installations back on only after the spray has evaporated.
- If using the product as a rust dissolver, wait for 5 to 10 minutes before proceeding.



BENEFITS:

- Excellent penetrating properties
- Moisture repellent
- Rust preventive
- Corrosion preventive
- Powerful jetspray
- 360° valve

TYPICAL PROPERTIES

Contents	Unit	400 ml
Basis		Mixture based on mineral oil
Density	g/ml	0.810
Propellant		Butane / Propane
pH		Neutral
Vapor Pressure at 20 °C	Bar	3 to 4
Flash Point	°C	52
Volume organic component (VOC)	%	83.6
Yield	g/sec	2.33