

DESCRIPTION:

Rymax White Grease is designed to reduce friction between load bearing moving metal surfaces and/or the combination of metal and plastic surfaces. Rymax White Grease also protects metal surfaces from corrosion.

Applications

- Metal to plastic connections Sliding bearings
- Metal to metal connections Roller bearings
- Door hinges Ball bearings
- Springs Stabilization rubbers
- Shock absorbers Worm wheels

How to use?

Before use, carefully read the directions on the packaging and act accordingly. The aerosol should have room temperature. Best processing temperature 5 to 30°C. Before use, shake the aerosol.

Apply the White Grease in a thin layer. Optimum lubrication is obtained after evaporation of the solvent



BENEFITS:

- Water repellent
- Nonconductive
- Corrosion prevention
- Outstanding mechanical and thermal stability
- Excellent adhesion
- Prevents wear and sticking
- High viscosity
- Resistant to weather influences
- Resistant to weak acids and bases
- Contains PTFE (polytetrafluorethen)

TYPICAL PROPERTIES

Contents	Unit	400 ml
Basis		Mineral oil with white lithium
Density	g/ml	0.723
Propellant		Butane / Propane
4 Ball EP-test ((ASTMD2596)	N	5800
Vapor Pressure at 20 °C	Bar	3 to 4
4 Ball Wear-test (ASTMD2266)	mm	0.73
Volume organic component (VOC)	%	80
pH		Neutral
Yield	g/sec	1.51